



r u b e
PRODUCTOS TÉCNICOS S.L.

Camino do bosque, 11
Apdo 73 - 36417 - Mos
Pontevedra - SPAIN
Tel: +34 986 344 090
Fax: +34 986 344 864
rube@rubept.com
www.rubept.com



TECHNICAL SPECIFICATION

ZINC OXIDE ACTIVE SEAL

DESCRIPTION

White powder with great dispersant power.

APPLICATIONS

Accelerant of vulcanization in rubber industry. It increases the resistance to abrasion and protects rubber against UV radiation.

Compound for manufacturing paints, plastics and chemical and pharmaceutical products.

CHARACTERISTICS

ZnO	99.7 % min.
Pb	0.120 % max.
Cu	0.0020 % max.
Cd	0.0001% max.
Mn	0.0001 % max.
Fe	0.0050 % max.
Activation surface	5.0m ² /g—7.0m ² /g
Calcination loss	0.10 % máx.
Residue Mesh 325	0.05 % máx.

OTHER INFORMATION

For more information, ask for the Material Safety Data Sheet. Check the label of the packaging.

The information of this specification is based in our knowledge. It refers only to the indicated product and it does not mean any guarantee of its particular qualities. The user must ensure the suitability and accuracy of this information related to the use of the product.