



r u b e
PRODUCTOS TÉCNICOS S.L.

Camíño do bosque, 11
Apdo 73 - 36417 - Mos
Pontevedra - SPAIN
Tel: +34 986 344 090
Fax: +34 986 344 864
rube@rubept.com
www.rubept.com



TECHNICAL SPECIFICATION

ZINC OXIDE GOLD SEAL

DESCRIPTION

White powder with great dispersant power.

APLICATIONS

Accelerant of vulcanization for rubber industry. It increases the resistance to abrasion and protects rubber from UV radiation.

Component for manufacturing paints, plastics and chemical and pharmaceutical products.

CHARACTERISTICS

ZnO	99.9 % min.
Pb	0.005 % max.
Cu	0.0001 % max.
Cd	0.0001% max.
Mn	0 % max.
Fe	0.001 % max.
Activation surface	3.5m ² /g—5.5m ² /g
Calination loss	0.05 % max.
Residue Mesh 325	0.02 % max.

OTHER INFORMATION

For more information, ask for the Material Safety Data Sheet. Check the label of the packaging.

The information of this specification is bases in our knowledge. It refers only to the mentioned product and does not mean any guarantee of its particular qualities. The user must ensure the suitability and accuracy of this information related to the specific use of the product.