



**r u b e**  
PRODUCTOS TÉCNICOS S.L.

Camino do bosque, 11  
Apdo 73 - 36417 - Mos  
Pontevedra - SPAIN  
Tel: +34 986 344 090  
Fax: +34 986 344 864  
rube@rubept.com  
www.rubept.com



## TECHNICAL SPECIFICATION

# ZINC OXIDE RED T2 SEAL

### DESCRIPTION

White powder with great disperdant power.

### APPLICATIONS

Accelerant of vulcanization in rubber industry. It increases the resistance to abrasión and protects rubber against UV radiation.

Compound for manufacturing paints, plastics and chemical and pharmaceutical products.

### CHARACTERISTICS

ZnO	99.0 %
Pb	0.350 %
Cu	0.0500 %
Cd	0.0200 %
Mn	0.0001 %
Fe	0.0700 % max.
Activation surface	3.5m <sup>2</sup> /g—5.5m <sup>2</sup> /g
Calcination loss	0.15 %
Residue Mesh 325	0.10 %

### OTHER INFORMATION

For more information, ask for the Material Safety data Sheet. Check the label of the packaging.

The information of this specification is based in our knowledge. It only refers to the indicated product and does not mean any guarantee of its particular qualities. The user must ensure the suitability and accuracy of this information related to the specific use of the product.