

Camiño do bosque, 11 Apdo 73 - 36417 - Mos Pontevedra - SPAIN Tel: +34 986 344 090 Fax: +34 986 344 864 rube@rubept.com





## **TECHNICAL DATA SHEET**

# **RUBEZINC 20**

### **DESCRIPTION**

White powder with greta dispersing power.

Zinc oxide especially formulated for different industrial process where economic cost is essential.

#### **APPLICATIONS**

Accelerator for vulcanization in rubbe rindustry. It increases the abrasion and protects rubber from UV radiation.

96.08 %

Component for manufacturing paints, plastics and chemical and pharmaceutical products.

### **CHARACTERISTICS**

ZnO

Pb	0.055 %
Cu	0.001 %
Cd	0.004 %
Fe	0.011 %
Volatile elements 825°C	8.20 / 7.75
Volatile elements 600°C	0.121 / 0.138
Particle > 45mm (%)	0.019
Soluble particles (%)	0.256 / 0.203
BET	0.22 / 4.26 (180°C)
ILT %	16.30 / 15.61
Real density	4.6353

# OTHER NFORMTION

For more information, check Material Safety Data Sheet. Check the label of the product.

The information of this Technical Data Sheet is based in our knowledge. It only refers to the indicated product and it doesn't mean any guarantee of its particular quality. The user must ensure that this information is accurate for the specific use of the product.