



r u b e

PRODUCTOS TÉCNICOS S.L.

Camino do bosque, 11
Apdo 73 - 36417 - Mos
Pontevedra - SPAIN
Tel: +34 986 344 090
Fax: +34 986 344 864
rube@rubept.com
www.rubept.com



TECHNICAL SHEET

SULPHUR 1/S

DESCRIPTION

Sulphur for industrial application, with high purity. Obtained after a refining and depurating process that guarantees its high purity and quality.

APPLICATIONS

In rubber industry, helping with the vulcanization process.

CHARACTERISTICS

Richness	>99.5 %
Oil	0.75 ± 2.0 %
Loss at 100°-105°C	< 0,3%
Silica	< 0,4%
Sieve pass (90 microns)	< 0,7%
Sieve pass (180 microns)	<0,05%

PRESENTATION AND STORAGE

It is packed in bags of 25 kg on pallet and shrink wrapped.

It is packed in Big-bags on pallet

It is recommended to use this product during the 12 months after production date (in normal storings conditions: inside warehouse, T°<25°C,...)

OTHER INFORMATION

For more information, check the Material Safety Data Sheet. Check also the label of the material.

The information of this document is based in our current knowledge. It refers only to the indicated product and it doesn't mean any guarantee of its particular quality. The user must ensure the suitability and accuracy of this information, related to the specific use he is going to give to the product.